

AUTOMATIC CONTROLLER



Automation ensures trouble free, consistent & repetitive operation. A basic RO plant will have level & pressure interlocks. Astero MP is a perfect controller for such basic automation & motor protection.

ASTERO CONTROLLER



ASTERO 1 MP/ 3 MP



	ASTERO 1 MP	ASTERO 3 MP
Panel Supply	230 V A.C. ±10% 50/60 Hz	415 V A.C. ±10% 50/60 Hz
Pump Configuration	1Φ	3Φ
Current Ranges	2-10 Amps	
Resetting	By power button ON/ OFF	
Flush time/Current Setting	Potentiometer on the panel	
HP Ranges	Up to 2HP	Up to 3HP
Dimensions	190(H) x 150(V) x 75mm deep	
Mounting	Wall/ Skid	
Indications	Overload	Overload/ Single Phase
	Power ON/ Pump ON/ RWT Level	
	Level of Product Tank/ Low Pressure/ HPS/ Auto Flushing	

• All dimensions are in mm.
H- horizontal, V- vertical

KEY ATTRIBUTES

- **RO LOGIC** programmed
- **IDEALLY SUITABLE FOR SMALL SIZE PLANTS**
- **AUTOMATICALLY FLUSHES** the membrane during starting/stopping(RO mode)
- **SEPARATE POWER & CONTROL TERMINAL**
- Can also be **CONFIGURED FOR FILTER/SOFTNER AUTOMATION**
- ideally suitable for **STAND ALONE FILTER SYSTEM**
- **EQUIPPED TO SUITE AUTO MULTI PORT VALVE(Auto mode)**
- **MOTOR PROTECTION INBUILT**