

TECHNICAL SPECIFICATIONS- EDOSE NEO			
MECHANICAL	Dosing Capacity @ 4Kg/Cm ²	LPH	1.5, 3, 6, & 10
	Max. Operating Pressure	Kg/Cm ²	7
	Max. Stroke Frequency	strokes/min	400
ELECTRICAL	Voltage	V	230 (+/- 20%)
	Length of main cable	m	2
	Max. power consumption	W	30
	Electric safety class	-	2
	Pollution degree	-	3
	Ingress Protection	IP	65
	Digital Display	Backlight LCD	Glass
SOUND	Max. sound pressure level	dB	< 60
MOC	Pump Head	PLASTICS	GF PP
	Diaphragm		PTFE
	Connectors		GF PP
	Suction/Discharge Tubing		PE
	Plunger	METALS	SS-304
	Copper		Class-H

Available with Your Trusted Partner for Water Treatment Solutions:

FILTRA CONSULTANTS AND ENGINEERS LTD.

Gala No. 2 & 3, Ground Floor, Neminath Industrial Estate No. 2, Navghar, Vasai (East), Dist.: Palghar - 401 219
 Tel.: +91 8691009127/26 Email: filtraw@gmail.com Website: www.ewater-treatmentindia.com

