

Salt Refractometer

RSM-1000



PRISM

Optical Glass Sensor

SAMPLE STAGE

Press a sample

LCD DISPLAY

Large, easy-to-read screen

Automatic backlight when ambient light is sensed

START

Press to measure a sample

STORE / RECALL

Store and read the measured values

ZERO

Use distilled or tap water to calibrate

DETACHABLE SLEEVE

Provides grip and additional protection

FEATURES:

- Range: 0.0 ~ 28.0%
- Resolution: 0.1%
- Accuracy: $\pm 0.2\%$
- ATC Function included (10 ~ 60°C)
- Temperature Range: 0 ~ 70°C
- Within 3 Seconds Measurement time
- Auto shut-off function after 2 minutes
- Automatic screen brightness control
- Data Store: Up to 20
- Usage Environment: 10 ~ 40 °C
- Idle Sample Volume: 0.5ml
- Unit: Water resistant (splash proof)
- Power Source 1.5V x 2(AAA alkaline)
- Size: 58(W) x 36(D) x 122(H)mm
- weight: 149g
(including batteries and detachable cover)



MEMBER



ISO 9001
certified company

Available with:

FILTRA CONSULTANTS AND ENGINEERS LTD.

Gala No. 2 & 3, Ground Floor, Neminath Industrial Estate No. 2, Navghar, Vasai (East), Dist.: Palghar - 401 219
Tel.: +91 8691009127/26 Email: filtraw@gmail.com Website: www.ewatertreatmentindia.com

