

UNIVERSAL INDICATOR

Our range of universal panel indicators is appreciated for its high accuracy, easy installation, compact design and optimum functionality. The models can be used for both simple 'measurement only' applications and in more demanding situations where digital communications, alarms and complex signal conditioning is required.

4-20mA OUTPUT from any FIELD TRANSMITTER



DATALOGGER DL-650 with 4 GB SD card



INDICATOR UT-650



MODEM



Data export to EXCEL FORMAT with Date & Time stamp



Annunciator/Hooter



4-20mA to CHART recorder



Mobile SMS



Published on Website

KEY ATTRIBUTES

- Suitable for 2/3/4 wire field transmitter
- **IN-BUILT 24V D.C. SUPPLY SOURCE** for field transmitter (like PO 600 or CI 550 24V D.C.)
- **RESOLUTION IS SETABLE FROM 0.001 TO 1**
- **IN-BUILT ALARM ANNUNCIATOR** with acknowledgment facility.
- Used to display parameter values like pH/ORP/ Conductivity/TDS/Pressure/Level/Temp./Flow/DO with 2 relay output for high & low set points
- **HYSTERISIS & CONTROL DELAY** Hysterisis is the percentage of set point below which relay will reset after getting energized
- Options of **RETRANSMISSION OF RS 485 OR 4-20MA O/P**

UT 650

Physical dimensions
Cut-out size
Enclosure
Mounting
Input supply
Alarms
Relay

Control operation
Accuracy
Display

Resolution
Calibration/set point
Output

105 x 105 x 130mm
90 x 90mm
ABS weather proof IP-65
Field/ Pipe/ Panel
230 V A.C./ 110 V A.C.
Separate LED indication for high & low
Individual high & low relay 5A@ 230V
(programmable through entire range with set-able control delay & hysteresis)
Alarm/auto reset/control
± 2% FS
4 digit 7 segment LED display
Dual Line Backlit LCD (optional)
0.001 to 1
Using front keypad
4-20 mA/RS485 (optional)

Available with: