



The Popular **@dose**<sup>®</sup> pump is now available in PVDF for Sulfuric Acid applications


## FEATURES



LCD Display



Frequency  
Up to 400 spm



Dosing rate  
1.5, 3.0, 6.0 & 10.0 LPH



Solid PTFE diaphragm for



Built-In Air Release



Dosing head conveniently located  
next to front controls for easy



Double ball NRV

Available with:

**FILTRA CONSULTANTS AND ENGINEERS LTD.**

Gala No. 2 & 3, Ground Floor, Neminath Industrial Estate No. 2, Navghar, Vasai (East), Dist.: Palghar - 401 219  
Tel.: +91 8691009127/26 Email: [filtraw@gmail.com](mailto:filtraw@gmail.com) Website: [www.ewatertreatmentindia.com](http://www.ewatertreatmentindia.com)





**For Sulfuric Acid Applications.**

- Wetted parts in PVDF.
- Polymer Coated Spring.
- Teflon Tubing.

**Technical Specifications**

TECHNICAL SPECIFICATIONS			
MECHANICAL	Dosing Capacity @ 4Kg/Cm <sup>2</sup>	LPH	6
	Max. Operating Pressure	Kg/Cm <sup>2</sup>	7
	Max. Stroke Frequency	strokes/min	400
ELECTRICAL	Voltage	V	230 (+/- 20%)
	Length of main cable	m	2
	Max. power consumption	W	30
	Electric safety class	-	2
	Pollution degree	-	3
	Ingress Protection	IP	65
SOUND	Max. sound pressure level	dB	< 60
MOC	Pump Head	PLASTICS	PVDF
	Diaphragm		PTFE
	Connectors		PVDF
	Suction/Discharge Tubing		PTFE

Available with: